

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/051165 A3

(51) International Patent Classification⁷: F24F 13/04, B01F 5/00

(21) International Application Number:
PCT/KR2002/002272

(22) International Filing Date: 3 December 2002 (03.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): LG ELECTRONICS INC. [KR/KR]; 20, Yoido-dong, Youngdungpo-gu, 150-721 Seoul (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LEE, Sung Hwa [KR/KR]; Towolsungwon Apt. 503-402, Sangnam-dong, Changwon-shi, 641-010 Kyongsangnam-do (KR). EOM, Yoon Seob [KR/KR]; Woosung Apt. 101-1006, Namyang-dong, Changwon-shi, 641-091 Kyongsangnam-do (KR).


(74) Agents: BAHNG, Hae Cheol et al.; KIMS INTERNATIONAL PATENT & LAW OFFICE, 15th Floor Yo Sam Building, 648-23, Yeoksam-dong, Kangnam-gu, 135-080 Seoul (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,

[Continued on next page]

(54) Title: FLOW SPREADING MECHANISM



(57) Abstract: The present invention relates to a flow spreading mechanism, in particular a flow spreading mechanism used with refrigerators or air conditioners to enhance spreading of cool or warm air. To achieve the above-mentioned object, this invention comprises at least one inlet (200) through which fluid flow comes in; a flow separator means (110) dividing the flow coming through the at least one inlet (200) into at least two separate flows; and an outlet (300) through which at least two of the at least two flows having been divided into separate flows by the flow separator means go out after they meet again, thereby forming complex vortices near the outlet, which make the flow going out of the outlet swing. Flow spreading mechanism of the present invention provides a better uniformity of temperature distribution for refrigerators or air conditioners, compared with the simple-ducted outlet of the prior art.

WO 2004/051165 A3



TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:

10 February 2005